


Dimensions in “mm”



Order example:

2 x LCW04 - 20kg


QuantityModelCapacity

Email to sales@loadcellsensor.com for a quote


Specifications			
Rated Capacity	3/6/10/20/40 kg		
Rated Output	≈2.0 mV/V	Compensated Temp.	-10...+40°C
Excitation	3~15V	Operating Temp.	-20...+60°C
Zero Balance	<0.4 mV/V	Temp. Coeff. of Zero	±0.005% F.S./°C
Nonlinearity	±0.02% F.S.	Temp. Coeff. of Span	±0.003% F.S./°C
Hysteresis	±0.02% F.S.	Input Resistance	405±30 Ohms
Nonrepeatability	±0.02% F.S.	Output Resistance	352±5 Ohms
Creep(30min)	±0.03% F.S.	Insulation Resistance	>2000M Ohms(50V)
Safe Load Limit	150% F.S.	IP Rating	IP65
Breaking Load	180% F.S.	Element Material	Aluminum alloy
Cable	Ø4*400mm 4-conductor		

• LCS reserves the right to modify its design and specifications without notice

Load direction



Wiring Code



Sensor/Amplifier/Indicator

Items	Power supply	Output/Function
LCW04	3-15V (Constant)	0...+30mV (Depending on the power supply)
LCW04 + Analog amplifier	12~24V DC	0-3.3V,0-5V,0-10V, 0-20mA,4-20mA...
LCW04 + Digital amplifier	12~24V DC	RS485 or RS232 output
LCW04 + Indicator	12~24V DC	Display force value Switch/Relay output Peak holding RS485/RS232 interface 0-5V/0-10V/4-20mA output
Email us for datasheet of amplifier and indicator		